

# ***Minuteman***<sup>®</sup>

## **390 Tank Vacuum Series**



*The 390 Series lets you select from three lid assemblies to work with one of 6 tank styles to create the vacuum that best fills your specific need.*



## 390 TANK VACUUM SERIES - VERSATILITY, POWER & PERFORMANCE

The 390 Series from Minuteman offers a wide range of vacuum systems for a variety of cleaning applications. Tank sizes range from 4 to 55 gallons and are available in painted, stainless steel and polyethylene.

Three separate vacuum motor assemblies are available with waterlifts of 85", 105" and 130", so the vacuum can be adapted to suit any cleaning job. All lid assemblies feature a Full-Bag Indicator light which alerts the operator when the disposable bag is full or when the cloth filter bag is clogged.

The 390 Series has many unique features over the competition. These vacuums have been designed with a patented self-sealing intake for a positive vacuum seal and can accommodate 1-1/4", 1-1/2" and 2" hoses, making it easily adaptable to any tool kit.

An exclusive embossed polyester filter bag protects the motor and float shut-off from lint and debris during wet recovery applications. The self-cleaning cloth filter bag keeps the cloth filter free of dirt and dust build-up.

The 390 - 15 gal or 20 gal units can be equipped with a wide area squeegee for picking up liquids on large floor areas. Available in two squeegee widths, 27-1/2" and 33" and various types of blades for different types of floors. The standard squeegee system pivots on any floor surface and allows the vacuum to be operated in both forward and reverse directions.

A wide variety of tools and attachments are available for use with the 390 Series. Tool Kits can include: dust brushes, crevice and upholstery tools, floor squeegees, brush floor tools, connectors and extenders and electric powerheads.

### SPECIFICATIONS FOR THE 390 SERIES

Model Number	Wet Capacity	Dry Capacity	Tank Size	Tank Material	Air Flow	Waterlift	Wheel Size (front/rear)
C39485-01	N/A	.75 cu. ft (.02 m <sup>3</sup> )	4 gal (15 ltr)	SS	95 CFM(2.7m <sup>3</sup> /min)	85" (2159 mm)	3/6" (8/15 cm)
C39485-03	N/A	.75 cu. ft (.02 m <sup>3</sup> )	4 gal (15 ltr)	PTD	95 CFM(2.7m <sup>3</sup> /min)	85" (2159 mm)	3/6" (8/15 cm)
C39685-01	5 gal (19 ltr)	1 cu. ft (.03 m <sup>3</sup> )	6 gal (22 ltr)	SS	95 CFM(2.7m <sup>3</sup> /min)	85" (2159 mm)	3/6" (8/15 cm)
C39685-03	5 gal (19 ltr)	1 cu. ft (.03 m <sup>3</sup> )	6 gal (22 ltr)	PTD	95 CFM(2.7m <sup>3</sup> /min)	85" (2159 mm)	3/6" (8/15 cm)
C39085-01	14 gal (53 ltr)	2.15 cu. ft (.06 m <sup>3</sup> )	15 gal (57 ltr)	SS	95 CFM(2.7m <sup>3</sup> /min)	85" (2159 mm)	3/8" (8/20 cm)
C39085-03	14 gal (53 ltr)	2.15 cu. ft (.06 m <sup>3</sup> )	15 gal (57 ltr)	PTD	95 CFM(2.7m <sup>3</sup> /min)	85" (2159 mm)	3/8" (8/20 cm)
C39085-05	14 gal (53 ltr)	2.15 cu. ft (.06 m <sup>3</sup> )	15 gal (57 ltr)	POLY	95 CFM(2.7m <sup>3</sup> /min)	85" (2159 mm)	5/5" (13/13 cm)
C39085-06	18 gal (68 ltr)	2.5 cu. ft (.07 m <sup>3</sup> )	20 gal (76 ltr)	POLY	95 CFM(2.7m <sup>3</sup> /min)	85" (2159 mm)	5/5" (13/13 cm)
C39330-01	28 gal (106 ltr)	4.36 cu. ft (.12 m <sup>3</sup> )	30 gal (113 ltr)	PTD	95 CFM(2.7m <sup>3</sup> /min)	85" (2159 mm)	5/5" (13/13 cm)
C39055-01	47 gal (178 ltr)	7.15 cu. ft (.20 m <sup>3</sup> )	55 gal (208 ltr)	PTD	95 CFM(2.7m <sup>3</sup> /min)	85" (2159 mm)	5/5" (13/13 cm)
C39055-07	33 gal (125 ltr)	7.2 cu. ft (.20 m <sup>3</sup> )	55 gal (208 ltr)	PTD	190CFM(5.4m <sup>3</sup> /min)	85" (2235 mm)	3/8" (8/20 cm)
C39105-01	14 gal (53 ltr)	2.15 cu. ft (.06 m <sup>3</sup> )	15 gal (57 ltr)	SS	115CFM(3.2m <sup>3</sup> /min)	105" (2667 mm)	3/8" (8/20 cm)
C39105-03	14 gal (53 ltr)	2.15 cu. ft (.06 m <sup>3</sup> )	15 gal (57 ltr)	PTD	115CFM(3.2m <sup>3</sup> /min)	105" (2667 mm)	3/8" (8/20 cm)
C39105-05	14 gal (53 ltr)	2.15 cu. ft (.06 m <sup>3</sup> )	15 gal (57 ltr)	POLY	115CFM(3.2m <sup>3</sup> /min)	105" (2667 mm)	5/5" (13/13 cm)
C39105-06	18 gal (68 ltr)	2.5 cu. ft (.07 m <sup>3</sup> )	20 gal (76 ltr)	POLY	115CFM(3.2m <sup>3</sup> /min)	105" (2667 mm)	5/5" (13/13 cm)
C39330-03	28 gal (106 ltr)	4.36 cu. ft (.12 m <sup>3</sup> )	30 gal (113 ltr)	PTD	115CFM(3.2m <sup>3</sup> /min)	105" (2667 mm)	5/5" (13/13 cm)
C39055-03	47 gal (178 ltr)	7.15 cu. ft (.20 m <sup>3</sup> )	55 gal (208 ltr)	PTD	115CFM(3.2m <sup>3</sup> /min)	105" (2667 mm)	5/5" (13/13 cm)
C39130-01	14 gal (53 ltr)	2.15 cu. ft (.06 m <sup>3</sup> )	15 gal (57 ltr)	SS	100CFM(2.8m <sup>3</sup> /min)	130" (3302 mm)	3/8" (8/20 cm)
C39130-03	14 gal (53 ltr)	2.15 cu. ft (.06 m <sup>3</sup> )	15 gal (57 ltr)	PTD	100CFM(2.8m <sup>3</sup> /min)	130" (3302 mm)	3/8" (8/20 cm)
C39130-05	14 gal (53 ltr)	2.15 cu. ft (.06 m <sup>3</sup> )	15 gal (57 ltr)	POLY	100CFM(2.8m <sup>3</sup> /min)	130" (3302 mm)	5/5" (13/13 cm)
C39130-06	18 gal (68 ltr)	2.5 cu. ft (.07 m <sup>3</sup> )	20 gal (76 ltr)	POLY	100CFM(2.8m <sup>3</sup> /min)	130" (3302 mm)	5/5" (13/13 cm)
C39330-05	28 gal (106 ltr)	4.36 cu. ft (.12 m <sup>3</sup> )	30 gal (113 ltr)	PTD	100CFM(2.8m <sup>3</sup> /min)	130" (3302 mm)	5/5" (13/13 cm)
C39055-05	47 gal (178 ltr)	7.15 cu. ft (.20 m <sup>3</sup> )	55 gal (208 ltr)	PTD	100CFM(2.8m <sup>3</sup> /min)	130" (3302 mm)	5/5" (13/13 cm)

SS= Stainless Steel; PTD= Painted; POLY= Polyethylene

# Minuteman®

**World Headquarters**  
**Minuteman International, Inc.**  
 111 South Rohlwing Road  
 Addison, IL 60101-4244  
 Telephone: (630) 627-6900  
 Fax: (630) 627-1130

**Minuteman Canada, Inc.**  
 2210 Drew Road  
 Mississauga, Ontario L5S 1B1  
 Telephone: (905) 673-3222  
 Fax: (905) 673-5161

#### 390 Lid Assemblies

**Model #85 Lid Assembly:** 85" waterlift, 95 CFM, 17,500 rpm, 2-stage fan, min. 1 hp input.

**Model#105 Lid Assembly:** 105" waterlift, 115 CFM, 17,500 rpm, 2-stage fan, min. 2.3 hp input.

**Model #130 Lid Assembly:** 130" waterlift, 100 CFM, 17,500 rpm, 3-stage fan, min. 2.3 hp input.