



# **TH20/TH28** Deluxe Orbital Floor Machine



FEATURES	TH20	TH28
Pad Size	20" x 14"	28" x 14"
Pad Speed	1740 RPM	1740 RPM
Amp Draw	7.1 Amp	7.8 Amp
Weight	250lbs	305lbs
Pad Pressure	0.89 lbs/in <sup>2</sup>	0.79 lbs/in <sup>2</sup>
Vibration Isolators	6 Primary / 8 Secondary	8 Primary / 8 Secondary
Motor	1.5 HP, 180 Frame, TEFC Dual Capacitor AC	
Power Source	115-230V, 60 Hz Power	
Power Cord	50 ft., (12-3) 2-Piece Industrial w/ Twist Lock	
Drive System	Eccentric Balanced Oribital Drive	
Sound Level (ave.)	60 dB – Meets GS42 Standard	

# Dry Stripping, Scrubbing and Sanding

The Minuteman TH20 is revolutionary. WD, Wheels down floating technology is the most productive orbital on the market. With over 0.79 pounds per sq. inch of pressure moving at over 1740 RPM, you will power through finish removal without chemicals. Scrub, strip, or sand floors effortlessly with less noise and fatigue.

#### **Power**

- 1.5HP, 180 frame. TEFC dual capacitor AC motor
- 115-230V, 60 Hz power
- 50ft. (12-3) 2-piece industrial power cord with twist lock
- Eccentric balanced design drive pads at 1740 RPM

## **Engineered Design**

- Dual vibration isolation system with industrial isolators
- Heavy -duty powder-coated steel handle with 5-position pin lock
- The WD handle is easy to remove for transport and storage
- The heavy-duty motor guard protects the motor from impact damage
- Thumb-operated safety switch. Dual steel operating triggers
- · Comfortable vinyl-dipped foam handle grip
- 2"x 8" non-marking ball bearing wheels
- Includes transport cart and drip tray
- Optional Active Vacuum Kit with 6 quart tank vacuum dust skirt, vacuum hoses and hardware (TH20 #TH1011/TH28 #TH1011-2814)
- Optonal Osprey Sprayer System includes motor-mounted sprayer pump, 4-gallon solution tank and hardware
- Optional Dust Control (TH20 #HP0031-DC-TH20/TH28 #HP0031-DC-TH28)

## **Safety Features**

Quiet 60 db operation. Meets GS42 standard



The 2" x 8" non-marking ball bearing wheels ensures a "clean" pass



